



NOTES:

1. CONCRETE MATERIAL SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 750 PSI (TO BE PROVIDED BY OTHERS)
2. REFER TO LOCATION SPECIFIC RISER DETAILS FOR ORIENTATION, DIMENSIONS, AND ATTACHMENT INFORMATION.
3. BACKFILL REQUIREMENTS SHALL FOLLOW ASTM D2321. IN THE EVENT OF DISCREPANCIES, ASTM D2321 SHALL SUPERCEDE THIS DETAIL.



SOLENO USA, LLC
66 DUPLAINVILLE RD.
SARATOGA SPRINGS, NY 12866
PHONE: (518) 682 - 0527

**REINFORCED TANGENTIAL RISER
WITH 24" LANDING**

DETAIL NUMBER	SCALE	DRAWN DATE	BY
D25-04	N.T.S.	2025-03-14	AND

© SOLENO INC. 2025. ANY USE OR REUSE OF THIS PLAN/DRAWING AND THE CORRESPONDING COMPUTER AIDED DESIGN/DRAFTING FILES WITHOUT THE EXPRESS WRITTEN CONSENT OF SOLENO INC. IS PROHIBITED. SOLENO INC. SHALL NOT BE RESPONSIBLE FOR ANY UNAUTHORIZED USE OR REUSE OF THESE MATERIAL, OR DAMAGES RESULTING THEREFROM.